

/// 5 AXLE 64,000L MULTI-COMPT TC 406 B-TRAIN MAXX TRAIN



Technical Specification	PL33403NA6RE & PR2290XNA6RE		
Model & Regulations	TC 406; ASME; CSA B620; CMVSS 121 (Brakes) CMVSS 108 (Electrical); ONT 413/O5 SPIF	Brakes	Drum with 16.5" x 7" H23 Extended Svc lining, Duralite steel Hubs w/ Outboard (Centrifuse) Brake Drums
Capacity & Compt	64,000L; 4, 5 & 6 Compartment B-Train Double Bulkheads w/ Baffles per Design	Wheels &Tires	8.25 x 22.5 Std Aluminum Wheels Michelin XTE 11R 22.5 14(G)
Tank Outer Shell Tank Framing	5454 H32 Alloy BTS Finish Alum Crossmembers & Outriggers per design	Wabco Brake System To CMVSS 121	ABS Wabco 2S/2M for the Lead & 2S/1M for the Pup
SUPER TANKER PKG Extended Warranty	SUPERTANKER 5 YEAR Limited Warranty on Dixon, Betts & FloTech Components	Air Tanks & Wiring	All Aluminum Air Tanks per Design Colour-Coded Air Lines per SAE Std
Manholes & Vents	Betts 20" 406-98 PAF Relief Aluminum Manholes, Betts AVT 3.5" ALTS Sequential Air Vapour Vents	KP Plates	Heavy Duty 3/8" Steel Construction w/ 2" King Pin & 3" Adjustable Bolt Holes
Overfill Protection	FloTech Optic Overfill Sensors per Compartment, Includes provisions for future retain sensors & monit	Lift Axles & Tire inflation	Provisions included for future installation of UBL lift axle w/ Wabco control system & Tiremax
Emergency Valves & Discharge System	Betts 4" Air Internal Valves w/ Tef-Sil Seals Dixon 4" API Adaptors w/ Baylast Seals	Landing Gear	Holland Mark V 200,000 LBS Two Speed w/ Non-Removeable Handle
Vapour Recovery System	Provision only. Outlet at the rear of the C/S overturn rail on the lead and pup	Paint	Steel & Frame Components Powder Coated Black. L/G & Axles OEM Armor Guard Finish
Piping System	4" Seamless Alum Sch 10 High Flow Piping Formed & Bent with Minimum Welding	Electrical & Lighting Systems CMVSS 108	Truck-Lite LED Lighting System with Fit n' Forget Harness system
Suspension Frame	Heavy Duty T100 & HLSA Steel Suspension Frame w/ Brackets for Huck Bolt-On Hanger Installation	Aluminum Cabinets	48" Curbside Storage & Control Cabinet on Lead 20" Curbside Control Cabinet on Pup
Suspension Tridem & Tandem Axle	HENDRICKSON INTRAXX AAT25K 14" RH, HXL-3 Wheel end system, 25,000 LBS Capacity, Bolt-C	Other Accessories	Aluminum Fenders, No Ladder Aluminum Hose Tubes & More
5th Wheel	Holland Kompensator FW35 w/Remote Grease Manifold	Documents	All Test & Certifications Documents Completed & Provide to the Customer